



NENUTEC NBFV8000 - ACTUATOR SELECTION TABLE

Actuator					IN PROGRESS					
					16Nm	24Nm	16Nm	24Nm	10Nm	15Nm
					90-120°	90-120°	90-120°	90-120°	90-120°	90-120°
Open-Closed	AC/DC 24V	90s	2-Point, 3-Point		NEAA24-16 NEAA24-16 S					
		140s	2-Point, 3-Point			NEAA24-24 NEAA24-24 S				
	65s 15s	2-Point, 3-Point						NESA24-10 NESA24-10S		
	120s 15s	2-Point, 3-Point							NESA24-15 NESA24-15S	
	145s 80s	2-Point, 3-Point				FSAA24-16 FSAA24-16 S				
	185s 130s	2-Point, 3-Point					FSAA24-24 FSAA24-24 S			
	AC 230V	90s	2-Point, 3-Point		NEAA230-16 NEAA230-16 S					
		140s	2-Point, 3-Point			NEAA230-24 NEAA230-24 S				
		65s 15s	2-Point, 3-Point						NESA230-10 NESA230-10S	
		120s 15s	2-Point, 3-Point							NESA230-15 NESA230-15S
Butterfly valve NBFV8000										
Type	DN [mm]	k_{vs} [m³/h]	max pressure							
NBFV 8040	40	50	16 bar	X		X		X		
NBFV 8050	50	85	16bar	X		X		X		
NBFV 8065	65	215	16 bar	X		X			X	
NBFV 8080	80	420	16bar	X		X			X	
NBFV 8100	100	800	16 bar		X		X			
NBFV 8125	125	1010	16bar		X		X			
NBFV 8150	150	2100	16 bar		X		X			