

TECHRITE

The Smart Pressure
Transducer
From Testo



The 549i smart high-pressure transducer allows you to connect to your smart device facilitating **data acquisition**, **record keeping** and **reporting** in one easy step.



Testo 549i

Smart Pressure Transducer

- Measurable media: Natural Gas, LPG, CFC, HFC, HCFC, N, H₂O, CO₂
- Hose-less, wire-less, pressure probe
- Compatibility: iOS 7.1 or newer/ Android 4.3 or newer and required mobile end device with Bluetooth 4.3 or newer
- Checking static gas pressure
- Differential pressure measurements
- Assessing blockages in filters or pipe work
- Setting operating pressure of gas appliances
- Gas tightness testing (including recording & logging longer tests where required by AS/NZ5601)
- Setting and checking set points on gas instruments (e.g. pressure switches & over-pressure shutoff devices)
- Logging gas pressure faults
- 0 to 60 bar range (with a 65 bar overload)
- Storage Temperature -20 to +60 °C
- Operating Temperature -20 to +50 °C
- Battery Type: 3 Micro batteries AAA

TECHRITE CONTROLS AUSTRALIA PTY. LTD.

Victoria - Head Office
12 Yiannis Court
Springvale, VIC 3171
Phone: +61 3 9549 4444
Fax: +61 3 9546 6069

New South Wales Office
Unit 10/19 Boden Road
Seven Hills NSW 2147
Phone: +61 2 9624 4486
Fax: +61 2 9624 6449

Queensland Office
Unit 20, 28 Burnside Road
Ormeau QLD 4208
Phone: +61 7 3807 9094
Fax: +61 7 3807 9095

Email: techrite@techrite.com.au

www.techrite.com.au